

SEP 10 2007

Customer No.: 31561  
Application No.: 10/708,805  
Docket No.: 12264-US-PAAMENDMENTIn the Claims:

Please amend the claims as follows:

09/11/2007 FCIMP 00000001 502X20 10700005  
02 FC:1201 200.00 PA

Claim 1 (currently amended) A system for accessing at least a first device and a second device in parallel, the first device and the second device being provided in parallel for the system, the system comprising:

a single shared bus, coupled to the first device;

a bus isolator, coupled to the shared bus and the second device for isolating the second device from the shared bus or connecting the second device to the shared bus; and

a control apparatus coupled to the shared bus so that the bus isolator isolates the second device from the shared bus when the control apparatus needs to access the first device and the bus isolator connects the second device with the shared bus when the control apparatus needs to access the second device.

Claim 2 (currently amended) The system of claim 1, wherein the control apparatus further comprises:

a bus exchanger, coupled to the single shared bus for switching the authority for the single shared bus between ~~different devices~~ the first device and the second device; and

a bus arbitrator, coupled to the bus exchanger so that the bus arbitrator controls the bus exchanger to connect the single shared bus with a circuit internally linked to the first device when the control apparatus needs to access the first device and the bus arbitrator

Customer No.: 31561  
Application No.: 10/708,805  
Docket No.: 12264-US-PA

controls the bus exchanger to connect the single shared bus with a circuit internally linked to the second device when the control apparatus needs to access the second device.

Claim 3 (previously presented) The system of claim 2, wherein a pre-defined isolation period must pass before the bus exchanger is permitted to switch the device for authority for the single shared bus.

Claim 4 (original) The system of claim 1, wherein the second device comprises a memory card compatible device.

Claim 5 (original) The system of claim 4, wherein the memory card compatible device is either a memory card or a card reader.

Claim 6 (original) The system of claim 1, wherein the first device comprises a memory device.

Claim 7 (currently amended) A control apparatus for accessing a plurality of devices in parallel through a single bus, the control apparatus connects to a first device through a shared bus and the control apparatus also connects to a second device through the shared bus and a bus isolator, the first device and the second device being accessed in parallel by the control apparatus, the control apparatus comprising:

Customer No.: 31561  
Application No.: 10/708,805  
Docket No.: 12264-US-PA

a bus exchanger, coupled to the shared bus for switching the authority of device for the shared bus; and

a bus arbitrator coupled to the bus exchanger such that the bus arbitrator controls the bus exchanger to connect with a circuit internally linked to the first device and to activate the bus isolator to isolate the second device from the shared bus when the control apparatus needs to access the first device and the bus arbitrator controls the bus exchanger to connect with a circuit internally linked related to the second device when the control apparatus needs to access the first device.

Claim 8 (original) The control apparatus of claim 7, wherein the bus exchanger is set to wait for the passage of a pre-defined isolation period lasting from the end of accessing the first device to the start of accessing the second device before switching the control of the shared bus from the first device to the second device.

Claim 9 (original) The control apparatus of claim 7, wherein the second device comprises a memory compatible device.

Claim 10 (original) The control apparatus of claim 7, wherein the memory compatible device is either a memory card or a card reader.

Customer No.: 31561  
Application No.: 10/708,805  
Docket No.: 12264-US-PA

Claim 11 (original) The control apparatus of claim 7, wherein the first device comprises a memory unit.

Claim 12 (currently amended) A system using a single bus for accessing a plurality of devices in parallel, comprising:

a memory unit;

a memory card compatible device;

a shared bus, coupled to the memory unit; and

a control apparatus coupled to the shared bus such that the control apparatus controls the shared bus to connect with a circuit internally linked to [[the]] a first device when the control apparatus needs to access the first device and the control apparatus controls the shared bus to connect with a circuit internally linked to [[the]] second device when the control apparatus needs to access the second device.

Claim 13 (original) The system of claim 12, wherein a pre-defined isolation period must pass before the control apparatus is permitted to access the second device through the shared bus.

Claim 14 (original) The system of claim 12, wherein the memory card compatible device is either a memory card or a card reader.

Customer No.: 31561  
Application No.: 10/708,805  
Docket No.: 12264-US-PA

Claim 15 (original) The system of claim 12, wherein the memory unit comprises read-only memory.

Claim 16 (currently amended) A system using a single bus for parallel accessing a plurality of devices, comprising:

a first device;

a second device;

a shared bus, coupled to the first device;

a bus isolator, coupled to the shared bus and the second bus for isolating the second device from the shared bus or connecting the second device to the shared bus; and

a control apparatus coupled to the shared bus so that the bus isolator isolates the second device from the shared bus when the control apparatus needs to access the first device and the bus isolator connects the second device with the shared bus when the control apparatus needs to access the second device, wherein the bus isolator is controlled by the control apparatus to isolate the first device and the second device from the shared bus in consideration of signaling demand for data transmission to prevent any data error resulting from a mutual interference of the signal transmission between the first device and the second device, wherein the first device and the second device are connected in parallel to the apparatus.

Customer No.: 31561  
Application No.: 10/708,805  
Docket No.: 12264-US-PA

Claim 17 (previously presented) The system of claim 16, wherein a triggering signal is transmitted to the bus isolator for performing the isolation.

Claim 18 (previously presented) The system of claim 16, wherein if the signaling demand for data transmission on the shared bus for the second device is lower than the first device, the bus isolator connects the second device with the shared bus immediately when the control apparatus carries out data transmission to the second device.

Claim 19 (previously presented) The system of claim 16, wherein a pre-defined isolation period is expired when the bus exchanger is permitted to switch the first device or the second device for authority for the shared bus.

Claim 20 (new) The system of claim 1 further comprising a first bus connecting the control apparatus and the first device for controlling the first device and a second bus connecting the control apparatus and the second device for controlling the second device.